

SOCKET CLIP™



A simple solution for integrating old slotted uprights with your upgraded Pipe & Base 2.0™ system. If you cross rent from companies that have not upgraded to Pipe & Base 2.0™ or if your company rents to other firms, the Socket Clip™ is a “must have” accessory.

The Socket Clip™ fits to any upright that has standard slots, allowing cross supports (sliders) fitted with Pipe & Base 2.0™ Ball Caps™ to connect to the slotted area of the upright.

Made from a specially formulated fiber infused Nylon compound, the Socket Clip™ is lightweight, and very strong. Rated to support a maximum load of twenty (20) pounds each, the Socket Clip™ will easily support standard velour or poly drapery.



Socket Clip™
Patent No.: US 9,211,027 B2




Socket Clip™ shown connected to a slotted upright, supporting a poly velour drape panel



VERSATOP™
SUPPORT SYSTEMS, LLC

3935 West Reno Ave, Suite C • Las Vegas, NV 89118
(p): 702-982-3311 • sales@versatop.com • www.versatop.com

SOCKET CLIP™



Approved Uses:



YES: Supporting a drape support rod is the **ONLY** approved use of the Socket Clip™.



NO: DO NOT use the Socket Clip™ to support any other attachment or part!



NO: DO NOT use the Socket Clip™ to support any other attachment or part!

Specifications:

Part Number:	111-100006
Fits:	All uprights with Standard Slots
Composition:	Reinforced fiber infused nylon compound designed for maximum wear resistance, strength and shape retention.
Weight:	.5 oz
Length:	2 in Overall
Width:	.75 in
Collar Inside Diameter:	NA
Socket Type:	Tapered .50 x 1.125 in
Lateral Socket Articulation:	50 degrees
Vertical Socket Articulation:	90 degrees up, 45 degrees down
Operating Temperature Range:	(-)30 deg F - (+)150 deg F
Supported Weight Limit:	20 pound maximum Downward Vertical weight limit each clip.

* Never exceed listed maximum weight limits. If using Versatop Support Systems components with components from other manufacturers, user should consult the manufacturers operating instructions for limitations. Limits for uprights or cross bars may be higher OR lower than the limits for the Socket Clip™. Always adhere to the safe weight limits provided by the pipe hardware manufacturer. The Socket Clip™ is to be used for supporting cross bars (Drape Support Rods) with standard drape, DO NOT use Socket Clips™ to support other accessories. NEVER use a Socket Clip™ that is damaged or has cracks in the clip area or body.

Fitting to slots:

Never force the clip into a slot that is too small to accommodate the top tab. Instead, trim the top tab according to the illustration above to achieve a smooth fit.



VERSATOP™
SUPPORT SYSTEMS, LLC

3935 West Reno Ave, Suite C • Las Vegas, NV 89118
(p): 702-982-3311 • sales@versatop.com • www.versatop.com